## **MINI ELECTRIC STACKER**

Ideal and handy choice for frequent lifting or for load weight max.150kg in industrial, laboratory, hospitals, office or other applicationsneed a compact design and effortless lifting.

Maintenance free batteries, fully automatic battery charger and non-marking wheels with wheel stops make the unit very easy and safe to operate and completely clean and nearly maintenance free.

NOBLELIFI

The smooth running castors enable it to cover medium length distances with ease.

Swivel castors enable the device to be positionedexactly at the workplace or for unloading goods without twisting the operator's back.





Mini Stacker 1KG=2.2LB 1INCH=25.4MM							
Identification	1.2	Manufacturer`s type designation		MES150	MES150A	MES150B	MES150/801
	1.4			hand			
	1.5	Load Capacity / rated load	Q(Kg)	150			
Weights	2.1	Service weight	kg	58	56	54	60
Wheels, Chassis	3.1	Tyres:solid, rubber,superelastic, pneumatic,polyurethane		Polyurethane			
	3.2	Tyre size,front	mm	75×32			
	3.3	Tyre size,rear	mm	100×32			
Basic Dimensions	3.5	Wheels, number		4			
	4.2	Lowered mast height	h₁(mm)	1958			
	4.4	Lift height	h <sub>3</sub> (mm)	1420	1435	1440	1400
	4.15	Lowered height	h <sub>13</sub> (mm)	130	115	110	65
	4.19	Overall length	I₁(mm)	880	865	920	920
	4.21	Overall width	b₁(mm)	520	500	500	801
	4.22	Fork dimensions	I(mm)	460	445	500	500
	4.25	Width over forks	b₅(mm)	520	400(⊕ 40×2)	Φ60	650
Performance Data	5.2	Lift speed, laden/unladen	mm/s	67/82			
	5.3	Lowering speed,laden/unladen	mm/s	96/89			
E-Motor	6.1	Lift motor rating	W	90			
	6.2	Battery acc.to BS,no		NO			
	6.3	Battery voltage, nominal capacity	V/AH	2X12/7			

